

Commerical LED Downlight Retrofit Kit

Part No: MLLG-SU-LED-DL[Size]-[watt]-[color] 902

Replaces: 100W Metal Halide



Specifications

Type	Commercial LED Downlight Retrofit Kit
Wattage	18-23
CRI	80+
Lumens	145-2050
Color Temperature	3000K 4000K
Life Hours	50,000 hours
Working Voltage	100-277V [D]
Power Factor	.95
THD	<20%
Operating Temperature	-10C to +50C
Operating Temperature	-10C to +50C
Dimmable	0-10V Optional
Dimensions	6 or 8 Inch Retrofit X 9.3 Inch H
Housing	Heavy gauge aluminum reflector
Mounting	Supplied with flexible metal conduit for connection to existing electrical junction box. Existing frame-in kits mounting method via frictions or clips
Warranty	5 years

Features

Designed for use with most existing architectural incandescent, fluorescent and metal halide housings.
Attach supply line to existing junction box through one of the knockouts provided in junction box. The existing socket whip and ballast can be set aside above the ceiling or removed completely
Aluminum extruded Heat sink designed to facilitate heat dissipation to reduce LED junction temperature for maintaining constant light output, color and life of solid state components
0-10V dimmable
Excellent Color Rendering, 80 CRI
Widely used in hospitality, commercial, and residential applications.

Model	Wattage	Size	Color
MLLG-SU-LED-DL6-18-[color]	18W	6 Inch	3000 or 4000
MLLG-SU-LED-DL8-18-[color]	18W	8 Inch	3000 or 4000
MLLG-SU-LED-DL8-23-[color]	23W	8 Inch	3000 or 4000