

## LED High Bay Light With Uplight

Part No: MLLG-AG-LED-HB-[Watts]-[Color]-[Voltage] 806

Replaces: 400W Metal Halide



### Specifications

Type	LED High Bay Lights - LED Warehouse Lighting
Wattage	100-200
CRI	70+
Lumens	14,000-28,000
Lumen Per Watt	140
Color Temperature	4000K   5000K
Beam Angle	120° With Up Light Option
Life Hours	100,000 hours
Replaces	400W Metal Halide
Working Voltage	100-277V [D]   347-480V [HV]
Frequency	50 / 60 hz
Power Factor	.90
THD	20% Max
Operating Temperature	-20° to +60° C
IP Rating	IP65
Dimmable	0-10V   Optional
Dimensions	16" x 8"
Net Weight	21
Housing	IP65 rated - Aluminum housing with Epoxy Coating
Mounting	Hook / Eye Mount (Standard), pendant mount (3/4 NPT), surface mount
Warranty	5 years

### Options

Ceiling Mount, pole mount (3/4 NPT), adjustable or wall mount options
[D] Dimming 0-10V
Motion sensor
50 or 90 degrees optics available
Frosted Lens
[ARL] Acrylic reflector and lens cover for up light (7.5% up/92.5% down)

### Order Code: MLLG-AG-LED-HB-[Watts]-[Color]

Watts	Color	Voltage
100	40 (4000K)	100-277
120	50 (5000K) *	347-480
150		
200		