

LED Parking Lot/Flood Light 80-150W

Part No: MLLG-AL-LED-SB-[Watts]-[Color] 1092

Replaces: 400W Metal Halide



Specifications

Type	LED Parking Lot Lighting
Wattage	80-150
CRI	70+
Lumens	11,200-21,000
Lumen Per Watt	140
Color Temperature	4000K 5000K
Beam Angle	120°
Life Hours	100,000 hours
Replaces	400W Metal Halide
Working Voltage	100-277V [D] 347-480V [HV]
Frequency	50-60Hz
Power Factor	.99
THD	15%
Operating Temperature	-30°F to +130°F
IP Rating	IP65
Dimmable	0-10V Optional
Dimensions	9"L X 13"W X 4" H
Housing	UL Listed for Wet Locations
Mounting	Arm Mount for Pole [ARM], Slip-fitter [SF]
Warranty	10 years

Features

Dark Sky Friendly Full cut-off. International Dark Sky Association Seal of Approval for dark sky friendly, full cut-off luminaries - Requires ARM Mount.
Die cast aluminum construction
Stainless steel external hardware
Finish Baked polyester powder coat
Certification UL Listed
IP65, Full Cut-Off
Standard color is Bronze

Model	Wattage	Lumens
MLLG-AL-LED-SB-80-[Color]	80W	11,200
MLLG-AL-LED-SB-100-[Color]	100W	14,000
MLLG-AL-LED-SB-120-[Color]	120W	16,800
MLLG-AL-LED-SB-150-[Color]	150W	21,000