

LED Parking Lot/Flood Light 150-300W

Part No: MLLG-AL-LED-SB2-[Watts]-[Color] 1090

Replaces: 1500W Metal Halide



Specifications

Type	LED Parking Lot Lighting
Wattage	150-300
CRI	70+
Lumens	22,950-45,900
Lumen Per Watt	150
Color Temperature	4000K 5000K
Beam Angle	Type V Standard - Special Order Type III or IV
Life Hours	100,000 hours
Replaces	1500W Metal Halide
Working Voltage	100-277V [D] 347-480V [HV]
Frequency	50-60Hz
Power Factor	.99
THD	15%
Operating Temperature	-30°F to +130°F
IP Rating	IP65
Dimmable	0-10V Optional
Dimensions	22"L X 14"W X 4" H
Housing	UL Listed for Wet Locations
Mounting	Arm Mount for Pole [-ARM], Slip-fitter [-SF]
Warranty	10 years

Options

Black [-BK] or White [-WH] Housing - Special Order
347-480VAC - Special order

Features

Dark Sky Friendly Full cut-off. International Dark Sky Association Seal of Approval for dark sky friendly, full cut-off luminaries
Die cast aluminum construction
Stainless steel external hardware
Finish Baked polyester powder coat
Certification UL Listed
IP65, Full Cut-Off
Standard color is Bronze
NEMA 3-Pin Socket and Shorting Cap Included

Model	Wattage	Lumens	DLC Qualified
MLLG-AL-LED-SB2-150-[Color]	150W	22,950	Yes
MLLG-AL-LED-SB2-200-[Color]	200W	30,600	Yes
MLLG-AL-LED-SB2-300-[Color]	300W	45,900	Yes