

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

46W 2x4 LED Edge Lit Panel - HO

Replaces: Fluorescent Troffer



Models and Specifications

Part Number	Watts	Lumens
MLLG-AG-LED-PAN-2X4-46-[COLOR]	46	5625
Replaces	Fluorescent Troffer	
Lumens Per Watt	125	
Voltage	100-277V [D]	
Frequency	50 / 60 hz	
Life Hours	50,000 hours	
Color Temperature	4000K 5000K	
CRI	80+	
Beam Angle	120°	
Operating Temperature	-14+104°F	
Dimmable	0-10V	
Housing	White Aluminum with White Prismatic Lens	
Mounting	Recessed/Drop In standard. Optional Suspension and Surface Mount Kits Available	
Dimensions	23.7 x 47.7 x 1.8	
Weight	0	
Warranty	5 years	

Features

- LED Edge Lit Panel with all aluminum frame white and painted; ultra thick for narrow plenums
- No UV or RF interference; Mercury-free
- Quiet and Flicker free
- Installation: flush mount standard suspension and surface mount optional
- Energy savings of over 60% compared to traditional fluorescent lamp
- Ideal for hotels meeting rooms offices school colleges/ universities and hospitals
- Protection Class: IP20

Options

Surface Mount

| Suspended Mount

|

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191