

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Bullet Flood Light

Replaces: 70W | 125W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Dimensions	Net Weight
MLLG-AD-LED-FLDB-15	15	1700	5" X 4.3" X 3"	1
MLLG-AD-LED-FLDB-28	28	3200 (5000K)	7.7" X 5.8" X 4.5"	2 lbs
Lumens Per Watt	113	<tr style="background-color:#D3D3D3">Voltage		
Frequency	50/60 hz	<tr style="background-color:#D3D3D3">.95		
Life Hours	70,000 hours	<tr style="background-color:#D3D3D3">3000K 5000K		
CRI	80+	<tr style="background-color:#D3D3D3">Beam Angle		
Operating Temperature	-40°F to +104°F	<tr style="background-color:#D3D3D3">IP65		
Dimmable	No	<tr style="background-color:#D3D3D3">Black or Bronze		
Mounting	Knuckle Mount	<tr style="background-color:#D3D3D3">6 years		

Features

- Integrated LED Flood Light for optimum lifetime performance of 10 years.
- Reduced energy consumption and operating costs by up to 80%.
- Maintenance free operation - lasts up to 6 times longer than conventional lighting
- Eligible for rebates
- Fantastic energy savings when compared to halogen and CFL floodlights
- Resistance to high and low temperatures
- NPS threaded locking swivel arm
- Suitable for uplighting & downlighting
- Suitable for wet locations
- L-70 Life 75 000 hrs

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191