


MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Billboard - Slipfitter Mount

Replaces: 400W | 1000W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Dimensions	Net Weight
MLLG-AX-LED-HMP2-120-[Color]-[Mount]	120	15000	16.54 X 12.88 X 2.76	16.6 lbs
MLLG-AX-LED-HMP2-160-[Color]-[Mount]	160	19920	18.9 X 12.88 X 2.76	18.67 lbs
MLLG-AX-LED-HMP2-200-[Color]-[Mount]	200	24600	21.26 X 12.88 X 2.76	20.13 lbs
MLLG-AX-LED-HMP2-240-[Color]-[Mount]	240	29520	23.62 X 12.88 X 2.76	23.0 lbs
MLLG-AX-LED-HMP2-280-[Color]-[Mount]	280	34200	25.98 X 12.88 X 2.76	24.45 lbs
MLLG-AX-LED-HMP2-320-[Color]-[Mount]	320	38760	30.71 X 12.88 X 2.76	28.5 lbs

Replaces	400W Metal Halide 1000W Metal Halide
Lumens Per Watt	140
Voltage	100-277V [D] 480V [HV]
Frequency	50-60Hz
Power Factor	> .95
THD	< 20%
Life Hours	70,000 hours
Color Temperature	4000K 5000K
CRI	75+
Beam Angle	Type 1,2,3,4,5 (15 distribution patterns available)
Operating Temperature	-40° C to +50° C
IP Rating	IP67
Dimmable	0-10V Optional
Housing	IP65 - Aluminum Alloy and PC Lens
Mounting	[PM] Pole Mount - Slipfitter
Warranty	10 years

Features

- Industry-leading LED lighting solution for ultra-high lumen output applications. Conforms to IEC/EN standards for wind force and vibration tests.
- Sleek design construction prevents build-up of dust particles and potentially damaging airborne particles.
- Minimum 100µm Corrosion resistant polyester powder coating. Certified according to 1000 hours salt spray testing standard ASTM B117 / ISO 9227:2012
- Proven IP67 ingress protection and IK08 mechanical impact resistance rated
- Adjustable yoke mounting bracket provides +/-75 rotation
- 15 light distributions are available for virtually any application
- 10 years warranty
- 15 distribution optical patterns available - call us

Options

Pole Arm [P]	Safety Cable	480VAC
10 kVa Surge Protection	20 kVa Surge Protection	Back Light Shield
Opt Colors: White, Black or Bronze		

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191