

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Outdoor Flood Light - Yoke Mount

Replaces: 400W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Dimensions
MLLG-AL-LED-FLD-20-[[Color]	20	1,600	7.1" x 5.5" x 4.3"
MLLG-AL-LED-FLD-30-[[Color]	30	2,400	7.1" x 5.5" x 4.3"
MLLG-AL-LED-FLD-50-[[Color]	50	4,000	8.9" x 7.3" x 4.9"
MLLG-AL-LED-FLD-75-[[Color]	75	6,000	11.2" x 9.3" x 5.5"
MLLG-AL-LED-FLD-100-[[Color]	100	8,000	11.2" x 9.3" x 5.5"
MLLG-AL-LED-FLD-150-[[Color]	150	12,000	14.36" X 11.44" X 6.77"

Replaces	400W Metal Halide
Lumens Per Watt	80
Voltage	100-277V [D]
Frequency	50/60 hz
Life Hours	30,000 hours
Color Temperature	4000K 5000K
CRI	75+
Beam Angle	120°
Operating Temperature	-40°C to +50°C
IP Rating	IP65
Dimmable	No
Housing	Black Aluminum and tempered glass
Mounting	Yoke with 1/2" Threaded Fitting
Weight	0
Warranty	5 years

Features

- MyLEDLightingGuide Integrated LED system for optimum lifetime performance of 10 years.
- Ideal for Parking Garages Warehouses apartments or any where you need light for an existing area.
- Instant on/off
- Reduced energy consumption and operating costs by up to 80%.
- Maintenance free operation - lasts up to 6 times longer than conventional lighting
- Solid state design and circuitry
- Great for shock and high vibration environments
- 50-80% reduced energy usage. Save money on your utility bill
- No humming or flickering.
- Cool beam - Does not produce Ultra Violet (UV) light or IR.
- Unique design with anodized Black housing for cooler operation and extended lamp life.
- Environmentally friendly fully recyclable no mercury or other hazardous materials

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191