

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED High Temperature Flood Lights - 75C

Replaces: 250W | 400W | 750W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces	Dimensions	Net Weight
MLLG-LED-HT75-100-[Color]-[Beam]	100	13000	250W	12.1x14.4x9.6"	17.2
MLLG-LED-HT75-150-[Color]-[Beam]	150	19500	400W	15.8x14.4x9.6"	20.5
MLLG-LED-HT75-200-[Color]-[Beam]	200	26000	750W	19.5x14.4x9.6"	23.6 lbs
Lumens Per Watt	130				
Voltage	100-277V [D] 277-480V [HV]				
Frequency	50 / 60 hz				
Power Factor	.95				
THD	20% Max				
Life Hours	50,000 hours				
Color Temperature	5000K				
CRI	70+				
Beam Angle	30° 90° 110° 150°				
Operating Temperature	-40° to +75°C				
IP Rating	IP66				
Dimmable	0-10V Optional				
Housing	IP66 rated - Massive Heat Sinks				
Mounting	Hook / Eye Mount (Standard)with Universal Bracket				
Warranty	5 years				

Features

- Massive custom heat sink allows this family of Industrial Flood Light to operate in temperatures from -40F to 167F.
- System Light Efficacy 130 LPW
- Multiple Choice of Optical Lenses
- Easy Installation & Maintenance
- Flexible Modular Design
- IP66
- Five Years Warranty

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191