

# MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

## LED High Temperature Flood Light

Replaces: 400W | 1000W Metal Halide



### Models and Specifications

Part Number	Watts	Lumens	Replaces	Dimensions	Net Weight
MLLG-LED-LS-FL-100-[Color]-HT	100	13,000	250W	12"X12"X 8.65"	13.2
MLLG-LED-LS-FL-150-[Color]-HT	150	19,500	400W	14.17"X13.77"X 8.65"	19
MLLG-LED-LS-FL-200-[Color]-HT	200	26,000	750W	18.11"X14.17"X8.65"	24.6
MLLG-LED-LS-FL-300-[Color]-HT	300	39,000	1000W	19.6"X16.53"X8.65"	38.3
MLLG-LED-LS-FL-400-[Color]-HT	400	52,000	1000W	22"X20.86"X8.65"	45.8

<b>Lumens Per Watt</b>	130
<b>Voltage</b>	100-277V [D]   347-480V [HV]
<b>Frequency</b>	50/60 hz
<b>Power Factor</b>	> .95
<b>THD</b>	< 15%
<b>Life Hours</b>	70,000 hours
<b>Color Temperature</b>	4000K   5000K   6500K
<b>CRI</b>	80+
<b>Beam Angle</b>	10° 25° 40° 60° 90° 120°
<b>Operating Temperature</b>	-85F to +190F [HT]
<b>IP Rating</b>	IP66
<b>Dimmable</b>	No
<b>Warranty</b>	5 years

### Features

- Massive custom heat sink allows this family of Industrial Indoor Bay Fixtures to operate in temperatures from -85F to 190F.
- ETL Listed with a 5 year warranty
- Hook mount trunnion mount or pendant adapter
- solid state design
- under driven components to maximize reduced heat production