

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Food Processing Light

Replaces: 250W | 400W | 750W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces
MLLG-LED-FD-100-[Color]-[Lens]	100	14,000	250W
MLLG-LED-FD-120-[Color]-[Lens]	120	16,800	400W
MLLG-LED-FD-150-[Color]-[Lens]	150	21,000	400W
MLLG-LED-FD-200-[Color]-[Lens]	200	28,000	750W
Lumens Per Watt	140		
Voltage	100-277V [D] 347-480V [HV]		
Frequency	50 / 60 hz		
Power Factor	.93		
THD	20% Max		
Life Hours	50,000 (L70) hours		
Color Temperature	5000K		
CRI	70+		
Beam Angle	50 90 120°		
Operating Temperature	-30° to +50°C		
IP Rating	IP66		
Dimmable	0-10V		
Housing	IP66 rated - Aluminum housing with Epoxy Coating		
Mounting	Hook / Eye Mount (Standard), pendant mount (3/4 NPT)		
Dimensions	19.25" x 7.8"		
Weight	16		
Warranty	5 years		

Features

- Easy to Clean
- High IP Rating able to withstand hot high pressure wash down
- No Exposed Screws
- No Glass
- No Toxic Chemicals in Material
- Stainless steel screws
- IP66 protection rating
- NSF Certified Food Processing Light

Options

Hook Mount

optics available

347-480V available on 100W, 120W and 150W (special order)

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191