

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Outdoor Flood Light - 15W-20W

Replaces: 175W Metal Halide



Models and Specifications

Part Number	Watts	Lumens
MLLG-GI-LED-FLD3-15	15	1261
MLLG-GI-LED-FLD3-20	20	1985
Replaces	175W Metal Halide	
Lumens Per Watt	95+	
Voltage	100-277V [D]	
Frequency	50/60 hz	
THD	< 15%	
Life Hours	50,000 hours	
Color Temperature	4000K 5000K	
CRI	75+	
Beam Angle	120°	
Operating Temperature	-35°C to +55°C	
IP Rating	IP65	
Dimmable	No	
Housing	Aluminum and tempered glass	
Mounting	trunion, 1/2" NPT threaded nipple available	
Dimensions	Depends on model - see chart	
Weight	0	
Warranty	6 years	

Features

- Integrated LED system for optimum lifetime performance of 10 years.
- Flood and Area Lighting ideal for Parking Garages Warehouses apartments or any where you need light for an existing area.
- Instant on/off
- Reduced energy consumption and operating costs by up to 80%.
- Maintenance free operation - lasts up to 6 times longer than conventional lighting
- Eligible for rebates
- 6 year warranty
- Warehoused in the USA - Ready to Ship.