

LED High Bay - Acrylic Dome

Part No: MLLG-GI-LED-HB-AP-[Watts]-[Color] 784

Replaces: 400W Metal Halide



Specifications

Part Number	MLLG-GI-LED-HB-AP-100-[Color]	MLLG-GI-LED-HB-AP-150-[Color]	MLLG-GI-LED-HB-AP-200-[Color]
Watts	100W	150W	200W
Lumens	12,861	18,300	23,910
Replaces	400W Metal Halide		
Lumens Per Watt	103		
Voltage	100-277V [D]		
Frequency	50-60Hz		
Power Factor	> .90		
THD	< 20%		
Life Hours	70,000 hours		
Color Temperature	5000K		
CRI	80+		
Beam Angle	120°		
Operating Temperature	-30°C to +60°C		
Dimmable	No		
Dimensions	16" W		
Net Weight	10		
Housing	Acrylic Shield		
Warranty	6 years		

Features

Integrated LED system for optimum lifetime performance of 20 years +.
Ideal for Warehouses, Factories, Distribution Centers or any where you need light for an existing area.
Reduced energy consumption and operating costs by up to 80%.
Maintenance free operation - lasts up to 10 times longer than conventional lighting
Solid state design and circuitry
Great for shock and high vibration environments
50-80% reduced energy usage. Save money on your utility bill
No humming or flickering.
Cool beam - Does not produce Ultra Violet (UV) light or IR.
Unique design with anodized silver housing for cooler operation and extended lamp life.
Environmentally friendly – fully recyclable, no mercury or other hazardous materials.