

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Stadium Light 300W-600W-900W

Replaces: 1000W | 1500W | 2000W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces	Dimensions	Net Weight
MLLG-AG-LED-HM-300-[Color]	300	40,500	1000W	20.6" X 11.3" X 6.8"	28.6 lbs
MLLG-AG-LED-HM-600-[Color]	600	78,000	1500W	22.2" X 23.5" X 15.7"	57.3 lbs
MLLG-AG-LED-HM-900-[Color]	900	117,000	2000W	31.1" X 23.5" X 15.7"	81.5 lbs

Lumens Per Watt	135
Voltage	100-277V [D] 347-480V [HV]
Frequency	50 / 60 hz
Power Factor	.93
THD	20% Max
Life Hours	50,000 (L70) hours
Color Temperature	4000K 5000K
CRI	70+
Beam Angle	15° 30° 65°X120° 30°X60°
Operating Temperature	-30°C to 50° C
IP Rating	IP66
Dimmable	Optional
Housing	IP66 rated - Aluminum housing with Epoxy Coating
Mounting	Trunion Mount - with rotating arm
Warranty	5 years

Features

- UL Approved Rebate Ready - Makes our LED High Mast eligible for utility rebates. This also signifies the product meets strict performance standards and is backed with a 5 year warranty.
- Eliminate Maintenance Costs and Labor - With a 50 000 (L70) hour rated life this means you will not be changing bulbs and ballasts for 10-15 years.
- Solid Construction - Aluminum housing with epoxy coating and a tough poly-carbonate prismatic lens.
- Ultra Efficient - 135 lumens / watt guarantees energy savings and a bright lit up space.
- Incredible Energy Savings - Up to 75% energy savings over metal halide high pressure sodium or mercury vapor bulbs. Even more when motion sensors or other smart controls are used.
- Bright and Crisp Light Output - High Color Rendering Index (CRI) means high quality crisp clear light.
- Versatile Applications - ports airports stadiums fields DOT roadway applications
- Installation Mounting Options - flexible trunion mount

Options

Trunion Mount with flexible pivot angles | 15° 30° 65°X120° 30°X60° | 480VAC Option