


300W LED UFO - replace 1000W HID

Part No: MLLG-AG-LED-HB-300-[Color]-[Beam]-[D] 980

Replaces: 1000W Metal Halide



Models

Part Number	Watts	Lumens
MLLG-AG-LED-HB-300-[Color]-[Beam]-[D]	300	45,000

Replaces	1000W Metal Halide
Lumens Per Watt	150
Voltage	100-277V [D] 347-480V [HV]
Frequency	50 / 60 hz
Power Factor	.90
THD	20% Max
Life Hours	100,000 (L70) hours
Color Temperature	4000K 5000K
CRI	70+
Beam Angle	120°
Operating Temperature	-30°C to 60° C
IP Rating	IP65
Dimmable	0-10V Optional
Housing	IP65 rated - Aluminum housing with Epoxy Coating
Mounting	Hook/Eye Mount (Standard), pendant mount (3/4 NPT), surface mount
Dimensions	16" x 8"
Weight	21
Warranty	5 years

Features

DLC Premium Qualified - Makes our fixture eligible for utility rebates. This also signifies the product meets strict performance standards and is backed with a 5 year warranty. And DLC Premium is super efficient, bigger rebates and more energy savings for you.
Eliminate Maintenance Costs and Labor - With a 50,000+ (L70)+hour rated life, this means you will not be changing bulbs and ballasts for 12+ years if your lights are turned on 12 hours a day, 365 days a year.
Solid Construction - Aluminum housing with epoxy coating and a tough poly-carbonate prismatic lens.
Ultra Efficient - 150 lumens / watt guarantees energy savings and a bright lit up space - making it the perfect 1000 watt high bay replacement for metal halide.
Incredible Energy Savings - Up to 75% energy savings over metal halide, high pressure sodium, or mercury vapor bulbs. Even more when motion sensors or other smart controls are used.

Options

Hook Mount, Ceiling Mount, pole mount (3/4 NPT) or wall mount options	50 or 90 degrees optics available	Frosted Lens	480VAC Option
Acrylic reflector and lens cover for Up Light (7.5% up / 92.5% down)	Motion Sensor (UL Listed)		