

UFO LED High Bay - 450W

Part No: MLLG-AG-LED-HB-[Watts]-[Color]-[Beam]-[D] 1150

Replaces: 1000W Metal Halide | 1500W Metal Halide | 2000W Metal Halide



Specifications

| | | |
|-----------------------|---|---------------------------------------|
| Part Number | MLLG-AG-LED-HB-450-[Color]-[Beam]-[D] | MLLG-AG-LED-HB-600-[Color]-[Beam]-[D] |
| Watts | 450W LED High Bay | 600W LED High Bay |
| Lumens | 72,000 | 96,000 |
| Replaces | 1000W Metal Halide 1500W Metal Halide 2000W Metal Halide | |
| Lumens Per Watt | 160 | |
| Voltage | 100-277V [D] 347-480V [HV] | |
| Frequency | 50 / 60 hz | |
| Power Factor | .93 | |
| THD | 20% Max | |
| Life Hours | 50,000 (L70) hours | |
| Color Temperature | 4000K 5000K | |
| CRI | 70+ | |
| Beam Angle | 30° 60° 120° | |
| Operating Temperature | -30°C to 50°C | |
| IP Rating | IP65 | |
| Dimmable | 0-10V | |
| Dimensions | 17.87"D x 9.61" | |
| Net Weight | 27 | |
| Housing | IP65 rated - Aluminum housing with Epoxy Coating | |
| Mounting | Hook/Eye Mount (Standard), pendant mount (3/4 NPT), surface mount | |
| Warranty | 5 years | |

Features

Rebate Eligible - Makes our 400+ Watt LED High Bay Lights eligible for utility rebates. This also signifies the product meets strict performance standards and is backed with a 5 year warranty. This is a must when you work with such powerful 400 watt LED high bay lights (and higher).

Eliminate Maintenance Costs and Labor - With a 50,000+ (L70)+hour rated life, this means you will not be changing bulbs and ballasts for 12+ years if your lights are turned on 12 hours a day, 365 days a year.

Solid Construction - Aluminum housing with epoxy coating and a tough poly-carbonate prismatic lens.

Ultra Efficient - 160 lumens / watt guarantees energy savings and a bright lit up space. Easily replace 1500W Metal Halide.

Incredible Energy Savings - Up to 75% energy savings over metal halide, high pressure sodium, or mercury vapor bulbs. Even more when motion sensors or other smart controls are used.

Options

| | | | |
|---|--|---------------|---------------------------|
| Hook Mount, Ceiling Mount, pole mount (3/4 NPT) | 30, 60 or 120 degrees optics available | 480VAC Option | Motion Sensor (UL Listed) |
|---|--|---------------|---------------------------|