

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED T5 HO Replacement

Replaces: 400W | 750W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces
MLLG-AG-LED-HBT5-[XX]-[Color]-[BA]-[D]	120	16,200	400W
MLLG-AG-LED-HBT5-[XX]-[Color]-[BA]-[D]	150	20,250	400W
MLLG-AG-LED-HBT5-[XX]-[Color]-[BA]-[D]	180	24,300	400W
MLLG-AG-LED-HBT5-[XX]-[Color]-[BA]-[D]	240	32,400	750W
Lumens Per Watt	up to 135		
Voltage	100-277V [D]		
Frequency	50 / 60 hz		
Power Factor	.90		
THD	20% Max		
Life Hours	50,000 (L70) hours		
Color Temperature	4000K 5000K		
CRI	70+		
Beam Angle	80°x100°, 30°x100°, 60°x120°		
Operating Temperature	-30°C to 50° C		
Dimmable	0-10V Optional		
Housing	Aluminum housing		
Mounting	cable mount		
Dimensions	depends on model		
Weight	0		
Warranty	5 years		

Features

- Designed to replace T5 High Bay Light Fixtures
- Part of a family of high performance Bay Lights
- High performance T5 high bay design with Nichia SMD
- Luminous flux up to 32 400lm (400W)
- Energy saving up to 90%
- CCT: 5000K (4000K available)
- CRI Ra70 (CRI Ra80 optional)
- Superior uniformity

Options

Emergency Backup (EMB)	Cable Mount	80°x100°, 30°x100°, 60°x120°
Controls Ready Options		

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191