

Industrial LED UFO with Uplight

Part No: MLLG-AG-LED-HB-[Watts]-[Color]-[V]-[BA] 806

Replaces: 250W | 400W | 750W Metal Halide



Models

Part Number	Watts	Lumens	Replaces
MLLG-AG-LED-HB-100-[Color]-[V]-[BA]	100	14,000	250W
MLLG-AG-LED-HB-120-[Color]-[V]-[BA]	120	16,900	400W
MLLG-AG-LED-HB-150-[Color]-[V]-[BA]	150	21,000	400W
MLLG-AG-LED-HB-200-[Color]-[V]-[BA]	200	28,000	750W

Lumens Per Watt	140
Voltage	100-277V [D] 347-480V [HV]
Frequency	50 / 60 hz
Power Factor	.90
THD	20% Max
Life Hours	100,000 hours
Color Temperature	4000K 5000K
CRI	70+
Beam Angle	120° With Up Light Option
Operating Temperature	-30° to +60° C
IP Rating	IP65
Dimmable	0-10V Optional
Housing	IP65 rated - Aluminum housing with Epoxy Coating
Mounting	Hook / Eye Mount (Standard), pendant mount (3/4 NPT), surface mount
Dimensions	16" x 8"
Weight	0
Warranty	5 years

Features

DLC Listed - Makes our fixtures eligible for utility rebates. This also signifies the product meets strict performance standards and is backed with a 5 year warranty.
Eliminate Maintenance Costs and Labor - With a 100 000 (L70) hour rated life this means you will not be changing bulbs and ballasts for 12 years if your lights are turned on 12 hours a day 365 days a year.
Solid Construction - Aluminum housing with epoxy coating and a tough tempered glass lens (poly-carbonate prismatic lens optional).
Ultra Efficient - 140 lumens / watt guarantees energy savings and a bright lit up space.
Incredible Energy Savings - Up to 75% energy savings over metal halide high pressure sodium or mercury vapor bulbs. Even more when motion sensors or other smart controls are used.

Options

Emergency Backup (EMB)	Ceiling Mount, pole mount (3/4 NPT), adjustable or wall mount options	[D] Dimming 0-10V	Motion sensor
50 or 90 degrees optics available	Frosted Lens	[ARL] Acrylic reflector and lens cover for up light (7.5% up/92.5% down)	