

## UFO LED High Bay - White

Part No: MLLG-LED-HB4-[Watts]-[Color]-[Beam] 1180

Replaces: 250W Metal Halide | 400W Metal Halide | 750W Metal Halide



### Specifications

Part Number	MLLG-LED-HB4-150-[Color]-[Beam]	MLLG-LED-HB4-200-[Color]-[Beam]
Watts	150W	200W
Lumens	18,750	25,000
Replaces	250W Metal Halide   400W Metal Halide   750W Metal Halide	
Lumens Per Watt	125	
Voltage	100-277V [D]   277-480V [HV]	
Frequency	50 / 60 hz	
Power Factor	.90	
THD	20% Max	
Life Hours	50,000 hours	
Color Temperature	4000K   5000K	
CRI	70+	
Beam Angle	50° 90° 120°	
Operating Temperature	-30° to +50°C	
IP Rating	IP65	
Dimmable	0-10V   Optional	
Dimensions	11.5" x 7.52"	
Net Weight	0	
Housing	IP65 rated - Aluminum housing with Epoxy Coating - White	
Mounting	Hook / Eye Mount (Standard), pendant mount (3/4 NPT), surface mount	
Warranty	5 years	

### Features

DLC Listed - Makes our UFO LED High Bays eligible for utility rebates. This also signifies the product meets strict performance standards and is backed with a 5 year warranty.
Eliminate Maintenance Costs and Labor - With a 50,000+ (L70)+hour rated life, this means you will not be changing bulbs and ballasts for 12+ years in your high bay UFO LED lights if your fixtures are turned on 12 hours a day, 365 days a year.
Solid Construction - Aluminum housing with epoxy coating and a tough tempered glass lens (poly-carbonate prismatic lens optional).
Ultra Efficient - Our LED UFO high bay light offers 140 lumens / watt which guarantees energy savings and a bright lit up space.
Incredible Energy Savings - Up to 75% energy savings over metal halide, high pressure sodium, or mercury vapor UFO high bay bulbs. Even more when motion sensors or other smart controls are used.

### Options

Ceiling Mount, pole mount (3/4 NPT), adjustable or wall mount options	[D] Dimming 0-10V	Motion sensor	Daylight sensor
50 or 90 degrees optics available	Frosted Lens	[ARL] Acrylic reflector and lens cover for up light (7.5% up / 92.5% down)	