

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Parking Lot Light - Area Light

Replaces: 400W | 1000W Metal Halide



Models and Specifications

Part Number	Watts	Lumens
MLLG-USA-LED-AR2-160-[Color]	160	20,040
MLLG-USA-LED-AR2-180-[Color]	180	22,500
MLLG-USA-LED-AR2-200-[Color]	200	24,970
MLLG-USA-LED-AR2-240-[Color]	240	30,000
MLLG-USA-LED-AR2-260-[Color]	260	31,830
MLLG-USA-LED-AR2-280-[Color]	280	33,400
MLLG-USA-LED-AR2-320-[Color]	320	35,960
Replaces	400W Metal Halide 1000W Metal Halide	
Lumens Per Watt	125	
Voltage	100-277V [D] 347-480V [HV]	
Frequency	50-60Hz	
Power Factor	> .90	
THD	< 20%	
Life Hours	100,000 (L70) hours	
Color Temperature	3000K 4000K 5000K	
CRI	70+	
Beam Angle	Type 2,3,4,5 40° 55° 70°	
Operating Temperature	-40°C to +55°C	
IP Rating	IP67	
Dimmable	0-10V	
Housing	Spun-aluminum top is finished in polyester powder coat.	
Mounting	Yoke Mount, Slip fitter, Square Pole, Round Pole	
Dimensions	22.1"L X 15.7" W X 3.86"H	
Weight	21lbs	
Warranty	10 years	

Features

- Dark Sky Friendly Full cut-off
- Snap action door latch for tool-less re-lamping
- Die cast aluminum construction
- Stainless steel external hardware
- Removable hinged door
- Ballast mounted directly to housing
- Two bolt keyhole mounting
- Finish Baked polyester powder coat

Options

Photocell	Dimming	Motion Sensor
Surge Protection	Round Pole Mount	

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191