

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Canopy - Square - 12"

Replaces: 100W | 175W | 250W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces
MLLG-USA-LED-CAN12-25	25	3100	100W
MLLG-USA-LED-CAN12-40	40	4960	175W
MLLG-USA-LED-CAN12-50	50	6200	250W
Lumens Per Watt	124		
Voltage	100-277V [D]		
Frequency	50-60Hz		
Power Factor	> .90		
THD	< 20%		
Life Hours	100,000 hours		
Color Temperature	4000K 5000K		
CRI	80+		
Beam Angle	Type 5		
Operating Temperature	-40°C to +50°C		
IP Rating	IP65		
Dimmable	0-10V		
Housing	UL Listed for Wet Locations		
Dimensions	12.3" X 12.3" x 8.78"		
Weight	14		
Warranty	10 years		

Features

- Field Select Driver (25W-40W-50W) - Preset to 50W
- LED Canopy with heavy duty die-cast finished in dark bronze
- One piece silicone gasket seals perimeter to prevent moisture and contaminants from entering the luminaire.
- Lens is clear prismatic polycarbonate and UV stabilized.
- CSA listed suitable for wet locations
- Four 1/2 coin plugs in each quadrant for easy conduit access.
- Vertical lamp position for true Type V distribution.
- CRI: 84