

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

Low Profile LED Canopy - USA Made

Replaces: 100W | 150W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces
MLLG-USA-LED-CANLP-36	36	4282	100W
MLLG-USA-LED-CANLP-50	50	5590	150W
Lumens Per Watt	112		
Voltage	100-277V [D]		
Frequency	50-60Hz		
Power Factor	> .90		
THD	< 20%		
Life Hours	100,000 hours		
Color Temperature	4000K 5000K		
CRI	80+		
Beam Angle	120°		
Operating Temperature	-40°C to +50°C		
IP Rating	IP65		
Dimmable	0-10V		
Housing	Powder coated aluminum housing and UL Listed for Wet Locations		
Mounting	Surface Mount		
Dimensions	12"D X 12"W X 2.8"H		
Weight	15 lbs		
Warranty	10 years		

Features

- MyLEDLightingGuide Low Profile LED Canopy - USA Made
- IP65 rated when used in under canopy application
- UV stabilized one-piece polycarbonate lens
- Powder coated aluminum housing
- Robust design for superb durability
- Flush J-box mounting standard available with Stem (shipped separately)

Options

Stem Mount