

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

USA Made Low Profile LED Canopy

Replaces: 150W | 175W | 250W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces
MLLG-USA-LED-CANLP2-40	40	4800	150W
MLLG-USA-LED-CANLP2-60	60	6300	175W
MLLG-USA-LED-CANLP2-80	80	8200	250W

Lumens Per Watt	115
Voltage	100-277V [D]
Frequency	50-60Hz
Power Factor	> .90
THD	< 20%
Life Hours	100,000 hours
Color Temperature	3000K 4000K 5000K
CRI	80+
Beam Angle	120°
Operating Temperature	-40°C to +50°C
IP Rating	IP65
Dimmable	0-10V
Housing	Powder coated aluminum housing and UL Listed for Wet Locations
Mounting	Surface Mount, Pendant Mount
Dimensions	12.25"D X 12.25"W X 2.4"H
Weight	15 lbs
Warranty	10 years

Features

- MyLEDLightingGuide Low Profile LED Canopy - USA Made
- IP65 rated when used in under canopy application
- Powder coated aluminum housing
- Robust design for superb durability
- Flush J-box mounting standard available with Stem (shipped separately)

Options

Stem Mount

| Motion Sensor

|