

# MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

## Recessed LED Canopy - USA Made

Replaces: 100W | 150W Metal Halide



### Models and Specifications

Part Number	Watts	Lumens	Replaces
MLLG-USA-LED-CANR-36	36	4282	100W
MLLG-USA-LED-CANR-50	50	5590	150W
<b>Lumens Per Watt</b>	112		
<b>Voltage</b>	100-277V [D]		
<b>Frequency</b>	50-60Hz		
<b>Power Factor</b>	> .90		
<b>THD</b>	< 20%		
<b>Life Hours</b>	100,000 hours		
<b>Color Temperature</b>	4000K   5000K		
<b>CRI</b>	80+		
<b>Beam Angle</b>	120°		
<b>Operating Temperature</b>	-40°C to +50°C		
<b>IP Rating</b>	IP65		
<b>Dimmable</b>	0-10V		
<b>Housing</b>	Powder coated aluminum housing and UL Listed for Wet Locations		
<b>Mounting</b>	Surface Mount		
<b>Dimensions</b>	16"D X 15"W X 2.4"H		
<b>Weight</b>	15 lbs		
<b>Warranty</b>	10 years		

### Features

- LED Recessed Canopy Light IP65 rated when used in under canopy application
- UV stabilized one-piece polycarbonate lens
- Powder coated aluminum housing
- Robust design for superb durability