

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Surface Mount Canopy Light

Replaces: 100W | 150W | 175W | 250W | 400W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces
MLLG-LED-CANS2-20-[Color]	20	2,520	100
MLLG-LED-CANS2-30-[Color]	30	3,780	150
MLLG-LED-CANS2-40-[Color]	40	5,040	175
MLLG-LED-CANS2-55-[Color]	55	6,552	250
MLLG-LED-CANS2-80-[Color]	80	10,080	400
Lumens Per Watt	125		
Voltage	100-277V [D] 347-480V [HV]		
Frequency	50-60Hz		
Power Factor	> .90		
THD	< 20%		
Life Hours	50,000 hours		
Color Temperature	4000K 5000K		
CRI	75+		
Beam Angle	120°		
Operating Temperature	-35°C to +55°C		
IP Rating	IP65		
Dimmable	Optional		
Housing	Bronze die cast aluminum housing and Heat/Shock Resistant. UL Listed for Wet Locations		
Dimensions	10.5"L x 10.5"W x 4.0"H		
Weight	0		
Warranty	6 years		

Features

- LED Canopy with heavy duty die-cast finished in dark bronze
- One piece silicone gasket seals perimeter to prevent moisture and contaminants from entering the luminaire
- Lens is clear prismatic poly-carbonate and UV stabilized
- UL 1598 listed for wet locations when wall mounted or in covered ceiling applications
- 1/2 coin plugs in each quadrant for easy conduit access

Options

Photocell

| Motion Sensor

|