

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Round Explosion Proof Light - C1D2

Replaces: 175W | 250W Metal Halide



Models and Specifications

| Part Number | Watts | Lumens |
|------------------------------|--|--------|
| MLLG-N-LED-EXPL2-45-[Color] | 45 | 6,750 |
| MLLG-N-LED-EXPL2-65-[Color] | 65 | 10,030 |
| Replaces | 175W Metal Halide 250W Metal Halide | |
| Lumens Per Watt | 150+ | |
| Voltage | 100-277V [D] | |
| Frequency | 50-60Hz | |
| Power Factor | >.95 | |
| THD | < 10% | |
| Life Hours | 50,000 (L70) hours | |
| Color Temperature | 5000K | |
| CRI | 70+ | |
| Beam Angle | 110° | |
| Operating Temperature | -40°C to +55°C | |
| IP Rating | IP66 | |
| Dimmable | No | |
| Housing | Explosion Proof | |
| Mounting | Pendant, Bracket, Ceiling, Stanchion, Wall | |
| Dimensions | 10.2×5.9 in | |
| Weight | 9.26 | |
| Warranty | 7 years | |

Features

- MyLEDLightingGuide extremely efficient Explosion Proof HID Replacement easily replace up to 250W HID.
- High Luminous efficacy up to 150lm/W
- Low profile and compact design.
- Heavy duty anodized die casting aluminum fixture.
- Shock and vibration resistant.
- Class I Division 2 Group A B C D
- Class II Division 1 Group E F G
- Class II Division 2 Group F G
- Class III Division 1
- CSA C22.2 No. 137-M1981 No. 250.0
- UL Ratings: 1598A 1598 8750 844