

# MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

## LED Round Back Medium Flood

Replaces: 100W | 150W | 175W | 250W Metal Halide



### Models and Specifications

Part Number	Watts	Lumens
MLLG-USA-LED-FLDRB-20-[Color]-[MT]	20	2,940
MLLG-USA-LED-FLDRB-30-[Color]-[MT]	30	3,480
MLLG-USA-LED-FLDRB-40-[Color]-[MT]	40	4,370
MLLG-USA-LED-FLDRB-60-[Color]-[MT]	60	7,010
MLLG-USA-LED-FLDRB-80-[Color]-[MT]	80	8,930
<b>Replaces</b>	100W Metal Halide   150W Metal Halide   175W Metal Halide   250W Metal Halide	
<b>Lumens Per Watt</b>	111	
<b>Voltage</b>	100-277V [D]	
<b>Frequency</b>	50-60Hz	
<b>Power Factor</b>	> .90	
<b>THD</b>	< 20%	
<b>Life Hours</b>	100,000 hours	
<b>Color Temperature</b>	4000K   5000K	
<b>CRI</b>	80+	
<b>Beam Angle</b>	Type 4, 40°, 55°, 70°	
<b>Operating Temperature</b>	-40°C to +50°C	
<b>IP Rating</b>	IP65	
<b>Dimmable</b>	0-10V	
<b>Housing</b>	UL Listed for Wet Locations. Bronze Color	
<b>Mounting</b>	Standard: Heavy Duty Adjustable Knuckle (HK). Optional: Slip Fitter (SF), Post Top Fitter (PT), Ground Stake Top Fitter (GS) or Yoke Mount (YM)	
<b>Dimensions</b>	9.72"L X 8.78 W X 8.58"H	
<b>Weight</b>	13	
<b>Warranty</b>	10 years	

### Features

- Rugged cast aluminum round back housing protects internal components
- Die-cast aluminum door with twin screw enclosure and hinged bottom
- Tempered impact resistant glass lens with weather tight gasket seal
- Large .5 universal aiming swivel knuckle with various mounting adapters
- Wide uniform beam for signs facades and small areas
- UL 1598 listed for wet locations

### Options

Photocell	Slip-fitter mount	Post Top Fitter mount
Ground Stack Top Fitter mount	Yoke Mount	Glare Shield

Product enhancements may result in specification changes without notice. Contact us for the latest information

[www.MyLEDLightingGuide.com](http://www.MyLEDLightingGuide.com) (888) 423-3191