

## Performance LED PL lamps Horizontal Mount

Part No: MLLG-GI-LED-PLH-[Base]-[Watts]-[Color] 988

Replaces: 36W CFL



### Models

| Part Number                       | Watts | Lumens |
|-----------------------------------|-------|--------|
| MLLG-GI-LED-PLH-[Base]-6-[Color]  | 6     | 65     |
| MLLG-GI-LED-PLH-[Base]-8-[Color]  | 8     | 850    |
| MLLG-GI-LED-PLH-[Base]-11-[Color] | 11    | 1250   |

|                       |  |
|-----------------------|--|
| Replaces              | 36W CFL  |
| Lumens Per Watt       | 100+   |
| Voltage               | 100-277V [D]   |
| Frequency             | 50 / 60 hz   |
| Power Factor          | .90  |
| Life Hours            | 50,000 hours   |
| Color Temperature     | 3000K   4000K   5000K   6000K                              |
| CRI                   | 80+  |
| Beam Angle            | 120 - Horizontal Fixture Mount                             |
| Optics                | Performance LED PL lamps                                   |
| Operating Temperature | -20°C to +40°C   |
| Dimmable              | No   |
| Housing               | Plastic / Aluminum   |
| Mounting              | G24D, G24Q, GX24Q, GX23 and G23 with 270 deg rotating base |
| Warranty              | 5 years  |

### Features

|   |
|---|
| Horizontal Mount  |
| G24 G23 and GX23 base and 120 Beam angle  |
| Does not produce Ultra Violet (UV) light rays   |
| Instant on/off  |
| Heat sink and custom optics for greater light dispersion longer life than incandescent & fluorescents |
| Wide voltage and constant current design  |
| Solid state design and circuitry  |
| High shock & vibration resistant  |
| Does not contain mercury or other harmful metals-ROHS Compliant                                       |
| 50-80% reduced energy usage.  |
| Save money on your utility bill   |
| No humming or flickering  |