

Performance LED PL lamps Horizontal Mount

Part No: MLLG-GI-LED-PLH-[Base]-[Watts]-[Color] 988

Replaces: 36W CFL



Specifications

| Part Number | MLLG-GI-LED-PLH-[Base]-6-[Color] | MLLG-GI-LED-PLH-[Base]-8-[Color] | MLLG-GI-LED-PLH-[Base]-11-[Color] |
|-----------------------|--|----------------------------------|-----------------------------------|
| Watts | 6W | 8W | 11W |
| Lumens | 65 | 850 | 1250 |
| Replaces | 36W CFL | | |
| Lumens Per Watt | 100+ | | |
| Voltage | 100-277V [D] | | |
| Frequency | 50 / 60 hz | | |
| Power Factor | .90 | | |
| Life Hours | 50,000 hours | | |
| Color Temperature | 3000K 4000K 5000K 6000K | | |
| CRI | 80+ | | |
| Beam Angle | 120 - Horizontal Fixture Mount | | |
| Optics | Performance LED PL lamps | | |
| Operating Temperature | -20°C to +40°C | | |
| Dimmable | No | | |
| Net Weight | 1 | | |
| Housing | Plastic / Aluminum | | |
| Mounting | G24D, G24Q, GX24Q, GX23 and G23 with 270 deg rotating base | | |
| Warranty | 5 years | | |

Features

| |
|--|
| <ul style="padding-left:20px"> Horizontal Mount |
| G24, G23 and GX23 base and 120 Beam angle |
| Does not produce Ultra Violet (UV) light rays |
| Instant on/off |
| Heat sink and custom optics for greater light dispersion, longer life than incandescent & fluorescents |
| Wide voltage and constant current design |
| Solid state design and circuitry |
| High shock & vibration resistant |
| Does not contain mercury or other harmful metals-ROHS Compliant |
| 50-80% reduced energy usage. |
| Save money on your utility bill |
| No humming or flickering |