

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Outdoor Parking Fixture 80W-150W

Replaces: 250W | 400W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces
MLLG-AL-LED-SB-80	80	11,200	250W
MLLG-AL-LED-SB-100	100	14,000	400W
MLLG-AL-LED-SB-120	120	16,800	400W
MLLG-AL-LED-SB-150	150	21,000	400W
Lumens Per Watt	140		
Voltage	100-277V [D] 347-480V [HV]		
Frequency	50-60Hz		
Power Factor	.99		
THD	15%		
Life Hours	100,000 hours		
Color Temperature	4000K 5000K		
CRI	70+		
Beam Angle	120°		
Operating Temperature	-30°F to +130°F		
IP Rating	IP65		
Dimmable	0-10V Optional		
Housing	UL Listed for Wet Locations		
Mounting	Arm Mount for Pole [ARM], Slip-fitter [SF]		
Dimensions	9"L X 13"W X 4" H		
Weight	9		
Warranty	10 years		

Features

- LED Shoebox Dark Sky Friendly Full cut-off. International Dark Sky Association Seal of Approval for dark sky friendly full cut-off luminaires
- Requires ARM Mount.
- Die cast aluminum construction
- Stainless steel external hardware
- Finish Baked polyester powder coat
- Certification UL Listed
- IP65 Full Cut-Off
- Standard color is Bronze

Options

Slip Fitter Mount	Arm Mount	Motion Sensor
Photocell	Wall Bracket	

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191