

LED Outdoor Parking Fixture 80W-150W

Part No: MLLG-AL-LED-SB-[Watts] 1092

Replaces: 250W Metal Halide | 400W Metal Halide



Models

Part Number	Watts	Lumens	Replaces
MLLG-AL-LED-SB-80-[Color]	80	11,200	250W
MLLG-AL-LED-SB-100-[Color]	100	14,000	400W
MLLG-AL-LED-SB-120-[Color]	120	16,800	400W
MLLG-AL-LED-SB-150-[Color]	150	21,000	400W

Lumens Per Watt	140
Voltage	100-277V [D] 347-480V [HV]
Frequency	50-60Hz
Power Factor	.99
THD	15%
Life Hours	100,000 hours
Color Temperature	4000K 5000K
CRI	70+
Beam Angle	120°
Operating Temperature	-30°F to +130°F
IP Rating	IP65
Dimmable	0-10V Optional
Housing	UL Listed for Wet Locations
Mounting	Arm Mount for Pole [ARM], Slip-fitter [SF]
Dimensions	9"L X 13"W X 4" H
Weight	9
Warranty	10 years

Features

Dark Sky Friendly Full cut-off. International Dark Sky Association Seal of Approval for dark sky friendly, full cut-off luminaries - Requires ARM Mount.
Die cast aluminum construction
Stainless steel external hardware
Finish Baked polyester powder coat
Certification UL Listed

Options

Slip Fitter Mount	Arm Mount	Motion Sensor	Photocell
Wall Bracket			