

## LED Parking Lot/Flood Light 80-150W

Part No: MLLG-AL-LED-SB-[Watts]-[Color] 1092

Replaces: 400W Metal Halide



### Specifications

Part Number	MLLG-AL-LED-SB-80-[Color]	MLLG-AL-LED-SB-100-[Color]	MLLG-AL-LED-SB-120-[Color]	MLLG-AL-LED-SB-150-[Color]
Watts	80W LED Shoebox	100W LED Shoebox	120W LED Shoebox	150W LED shoebox
Lumens	11,200	14,000	16,800	21,000

Replaces	400W Metal Halide			
Lumens Per Watt	140			
Voltage	100-277V [D]   347-480 Volt LED Parking Lot Lights [HV]			
Frequency	50-60Hz			
Power Factor	.99			
THD	15%			
Life Hours	100,000 hours			
Color Temperature	4000K   5000K			
CRI	70+			
Beam Angle	120°			
Operating Temperature	-30°F to +130°F			
IP Rating	IP65			
Dimmable	0-10V   Optional			
Dimensions	9"L X 13"W X 4" H			
Net Weight	9			
Housing	UL Listed for Wet Locations			
Mounting	Arm Mount for Pole [ARM], Slip-fitter [SF]			
Warranty	10 years			

### Features

Dark Sky Friendly Full cut-off. International Dark Sky Association Seal of Approval for dark sky friendly, full cut-off luminaries - Requires ARM Mount.
Die cast aluminum construction
Stainless steel external hardware
Finish Baked polyester powder coat
Certification UL Listed

### Options

Slip Fitter Mount	Arm Mount	Motion Sensor	Photocell
Wall Bracket			