

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Outdoor Parking Fixture 150W-300W

Replaces: 400W | 750W | 1000W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces	Net Weight
MLLG-AL-LED-SB2-150	150	22,950	400W	24.3 lb
MLLG-AL-LED-SB2-200	200	30,600	750W	26.5 lb
MLLG-AL-LED-SB2-300	300	45,900	1000W	28.7 lb

Lumens Per Watt	150
Voltage	100-277V [D] 347-480V [HV]
Frequency	50-60Hz
Power Factor	.99
THD	15%
Life Hours	100,000 hours
Color Temperature	4000K 5000K
CRI	70+
Beam Angle	Type V Standard - Special Order Type III or IV
Operating Temperature	-30°F to +130°F
IP Rating	IP65
Dimmable	0-10V Optional
Housing	UL Listed for Wet Locations
Mounting	Arm Mount for Pole [-ARM], Slip-fitter [-SF]
Dimensions	22"L X 14"W X 4" H
Warranty	10 years

Features

- Dark Sky Friendly Full cut-off. International Dark Sky Association Seal of Approval for dark sky friendly full cut-off luminaries
- Die cast aluminum construction
- Stainless steel external hardware
- Finish Baked polyester powder coat
- Certification UL Listed
- IP65 Full Cut-Off
- Standard color is Bronze
- NEMA 3-Pin Socket and Shorting Cap Included

Options

Black [-BK] or White [-WH] Housing - Special Order	347-480VAC - Special order	Slip Fitter Mount
Arm Mount	Motion Sensor	Photocell
Wall Bracket		

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191