

LED Parking Lot/Flood Light 150-300W

Part No: MLLG-AL-LED-SB2-[Watts]-[Color] 1090

Replaces: 1500W Metal Halide



Specifications

Part Number	MLLG-AL-LED-SB2-150-[Color]	MLLG-AL-LED-SB2-200-[Color]	MLLG-AL-LED-SB2-300-[Color]
Watts	150W LED Parking Lot Light	200W LED Parking Lot Light	300W LED Parking Lot Light
Lumens	22,950	30,600	45,900
Replaces	1500W Metal Halide		
Lumens Per Watt	150		
Voltage	100-277V [D] 347-480V LED Parking Lot Light [HV]		
Frequency	50-60Hz		
Power Factor	.99		
THD	15%		
Life Hours	100,000 hours		
Color Temperature	4000K 5000K		
CRI	70+		
Beam Angle	Type V Standard - Special Order Type III or IV		
Operating Temperature	-30°F to +130°F		
IP Rating	IP65		
Dimmable	0-10V Optional		
Dimensions	22"L X 14"W X 4" H		
Net Weight	24.3 lb	26.5 lb	28.7 lb
Housing	UL Listed for Wet Locations		
Mounting	Arm Mount for Pole [-ARM], Slip-fitter [-SF]		
Warranty	10 years		

Features

Dark Sky Friendly Full cut-off. International Dark Sky Association Seal of Approval for dark sky friendly, full cut-off luminaries
Die cast aluminum construction
Stainless steel external hardware
Finish Baked polyester powder coat
Certification UL Listed

Options

Black [-BK] or White [-WH] Housing - Special Order	347-480VAC - Special order	Slip Fitter Mount	Arm Mount
Motion Sensor	Photocell	Wall Bracket	