

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Decorative Outdoor Post-Top Light

Replaces: 100W | 250W | 400W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces	Dimensions
MLLG-YA-LED-PTD-30	30	3450	100W	11.9 x 11.9 x 26
MLLG-YA-LED-PTD-60	60	6900	250W	11.9 x 11.9 x 26
MLLG-YA-LED-PTD-120	120	13,800	400W	11.9 x 11.9 x 26
Lumens Per Watt	115			
Voltage	100-277V [D] 347-480V [HV]			
Frequency	50-60Hz			
Power Factor	> .90			
THD	< 20%			
Life Hours	50,000 (L70) hours			
Color Temperature	3000K 4000K 5000K			
CRI	70+			
Beam Angle	Type 5			
Operating Temperature	-40°C to +45°C			
IP Rating	IP65			
Dimmable	0-10V Optional			
Housing	UL Listed for Wet Locations			
Mounting	Pole Top Mount			
Weight	0			
Warranty	5 years			

Options

Photocell

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191