

LED Outdoor Post-Top Fixture replaces 250

Part No: MLLG-YA-LED-PTP-[Watts] 1151

Replaces: 70W Metal Halide | 100W Metal Halide | 150W Metal Halide | 250W Me



Models

Part Number	Watts	Lumens	Replaces	Dimensions
MLLG-YA-LED-PTP-20	20	2300	70W	12.6X11.2X16.3
MLLG-YA-LED-PTP-35	35	4100	100W	12.6X11.2X16.3
MLLG-YA-LED-PTP-50	50	5800	150W	12.6X13.7X15.7
MLLG-YA-LED-PTP-100	100	11,600	250W	12.6X13.7X15.7

Lumens Per Watt	110+
Voltage	100-277V [D] 347-480V [HV]
Frequency	50-60Hz
Power Factor	> .90
THD	< 20%
Life Hours	50,000 (L70) hours
Color Temperature	3000K 4000K 5000K
CRI	70+
Beam Angle	Type 4, 5
Operating Temperature	-40°C to +45°C
IP Rating	IP65
Dimmable	0-10V Optional
Housing	UL Listed for Wet Locations
Mounting	Arm Mount for Pole
Weight	0
Warranty	5 years

Options

Mounting Option: Post Top, Trunnion, Slip fitter	Photocell		
--	-----------	--	--