

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Outdoor Pole Top Fixture

Replaces: 70W | 100W | 150W | 250W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces	Dimensions
MLLG-YA-LED-PTP-20	20	3600	70W	12.6X11.2X16.3
MLLG-YA-LED-PTP-35	35	4550	100W	12.6X11.2X16.3
MLLG-YA-LED-PTP-50	50	6500	150W	12.6X13.7X15.7
MLLG-YA-LED-PTP-100	100	13,600	250W	12.6X13.7X15.7
Lumens Per Watt	110+			
Voltage	100-277V [D] 347-480V [HV]			
Frequency	50-60Hz			
Power Factor	> .90			
THD	< 20%			
Life Hours	50,000 (L70) hours			
Color Temperature	3000K 4000K 5000K			
CRI	70+			
Beam Angle	Type 4, 5			
Operating Temperature	-40°C to +45°C			
IP Rating	IP65			
Dimmable	0-10V Optional			
Housing	UL Listed for Wet Locations			
Mounting	Arm Mount for Pole			
Weight	0			
Warranty	5 years			

Options

Mounting Option: Post Top, Trunnion, Slip fitter

Photocell