

140W LED Outdoor Shoebox Fixture

Part No: MLLG-LED-SB-140-[Color]-[Mount] 1033

Replaces: 400W Metal Halide



Models

| Part Number | Watts | Lumens |
|---------------------------------|-------|--------|
| MLLG-LED-SB-140-[Color]-[Mount] | 140 | 17,123 |

| | |
|-----------------------|--|
| Replaces | 400W Metal Halide |
| Lumens Per Watt | 132 |
| Voltage | 100-277V [D] |
| Frequency | 50-60Hz |
| Power Factor | > .92 |
| THD | < 15% |
| Life Hours | 100,000 (L70) hours |
| Color Temperature | 4000K 5000K |
| CRI | 70+ |
| Beam Angle | 120° |
| Operating Temperature | -35°C to +55°C |
| IP Rating | IP65 |
| Dimmable | 0-10V Optional |
| Housing | IP 65 Aluminum Alloy and PC Lens |
| Mounting | Shoe Box ARM Mount [ARM], Slip-Fitter Mount [SF], Trunion [TR] |
| Dimensions | 16.3"L x 12.3"W x 3.2"H |
| Weight | 17.5 lbs |
| Warranty | 6 years |

Features

| |
|--|
| Best solution to Parking Lots , roadways and campuses. |
| One-piece aluminum heat sink brings a better performance of thermal management. |
| Straight Pole Arm, Slipfitter or Trunion Mount. |
| Shoebox Light uses integrated heat sink instead of conventional modular design. |

Options

| | | | |
|----------------------|----------------|--------------------|------------------|
| Slip fitter Mount | Trunion Mount | Straight Arm Mount | Photocell Option |
| Motion Sensor Option | Dimming: 0-10V | | |