

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

Slim LED WallPack

Replaces: 70W | 100W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces
MLLG-USA-LED-WPS-12	12	1340	70W
MLLG-USA-LED-WPS-20	20	2040	100W
Lumens Per Watt	102		
Voltage	100-277V [D]		
Frequency	50-60Hz		
Power Factor	> .90		
THD	< 20%		
Life Hours	100,000 hours		
Color Temperature	5000K		
CRI	80+		
Beam Angle	Type 4		
Operating Temperature	-40°C to +40°C		
IP Rating	IP65		
Dimmable	0-10V		
Housing	UL Listed for Wet Locations		
Dimensions	6.1" W X 8.6" H X 2.76" D		
Weight	5		
Warranty	10 years		

Features

- Slim Design LED WallPack - Rebate eligible with utilities
- Photocell Standard UV-protected photocell lens
- Durable die-cast housing anti-static powder coated paint
- Highly thermal conductive material and high efficiency cooling system
- 0-10V Dimming Standard 100% down to 10%
- ETL Listed suitable for wet locations; IP65 rated
- 80 CRI provides excellent exterior color rendering

Options

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191