MY LED LIGHTING GUIDE YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Linear Vapor Tight Fixture - Quick Ship

Replaces: 150W Metal Halide





Models and Specifications

Part Number		Watts		Lumens
MLLG-AL-LED-LIN-VP-31W-[Co	olor]	31		3,410
Replaces	150W Meta	al Halide		
Lumens Per Watt	110			
Voltage	100-277V [D]		
Frequency	50-60Hz			
Power Factor	> .90			
Life Hours	50,000 hou	rs		
Color Temperature	4000K			
CRI	80+			
Beam Angle	120°			
Operating Temperature	-4°F to +104°F			
IP Rating	IP66			
Dimmable	No			
Housing	UL Listed for Damp Locations and Vibration Resistant, IP65, Vapor Proof, Hard Plastic - resistant to aging and warping and Transparent Diffuser for uniform light coverage			
Dimensions	47.2"x4.2"x3.3" 4.1 lbs			
Weight	4.4 lbs			
Warranty	5 years			

Features

- Low energy consumption
- Contemporary design
- 3 500K 4 000K & 5 000K available
- Luminous efficiency 110 lm/W
- Surface mounted luminaire
- Suitable for Wet Locations
- L-70 Life 90 000 hrs
- cULus certified