

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Industrial Vapor Tight

Replaces: 70W | 100W | 150W | 175W | 250W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Dimensions
MLLG-USA-LED-LIN-VPC-22	22	2720	24 X 6.6 X 5
MLLG-USA-LED-LIN-VPC-35	35	3670	48 X 6.6 X 5
MLLG-USA-LED-LIN-VPC-45	45	5850	48 X 6.6 X 5
MLLG-USA-LED-LIN-VPC-60	60	7340	48 X 6.6 X 5
MLLG-USA-LED-LIN-VPC-90	90	11,700	96 X 6.6 X 5

Replaces	250W Metal Halide
Lumens Per Watt	130
Voltage	100-277V [D]
Frequency	50-60Hz
Power Factor	> .90
Life Hours	100,000 hours
Color Temperature	4000K 5000K
CRI	80+
Beam Angle	120°
Operating Temperature	-30°C to +60°C
IP Rating	IP65
Dimmable	No
Housing	UL listed for wet locations, NSF Approved for Splash and Non-food Zones.
Warranty	10 years

Features

- Equipped with energy saving ballasts/complies with federal energy efficiency standards
- Reinforced fiberglass housing
- High impact acrylic/15% DR diffuser material standard. High impact 50% & 100% DR available
- Continuous polyurethane gasket formed to housing provides a seamless seal
- Watertight hubs standard at each end accepts .5 conduit
- Optional galvanized steel mounting brackets with each fixture
- Baked white enamel finish internal channel/high reflectance
- No holes required for surface/chain mounting

Options

Mounting Bracket

|0-10V Dimming

|Emergency Backup

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191