

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Outdoor Wall Pack Flood

Replaces: 400W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Dimensions
MLLG-LED-WPFL-40-[Color]	40	5,233	13.1"L x 9.5"W x 7.5"H
MLLG-LED-WPFL-60-[Color]	60	7,928	13.1"L x 9.5"W x 7.5"H
MLLG-LED-WPFL-80-[Color]	80	11,065	18.5"L x 9.5"W x 9.0"H
MLLG-LED-WPFL-100-[Color]	100	13,695	18.5"L x 9.5"W x 9.0"H
Replaces	400W Metal Halide		
Lumens Per Watt	130+		
Voltage	100-277V [D]		
Frequency	50-60Hz		
Power Factor	> .90		
THD	< 20%		
Life Hours	50,000 hours		
Color Temperature	4000K 5000K		
CRI	75+		
Beam Angle	120°		
Operating Temperature	-30°C to +45°C		
IP Rating	IP65		
Dimmable	No		
Housing	Die cast Aluminum with Bronze Powder Coat Finish		
Mounting	Wall Mount		
Weight	0		
Warranty	6 years		

Features

- Heavy duty die cast aluminum housing.
- .5 threaded conduit entry with coin plug.
- Clear glass reflector is thermal/shock resistant.
- UL 1598 listed for wet locations.
- Dark bronze polyester powder finish for excellent impact corrosion and UV resistance.