

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

18" LED WallPack - Flood

Replaces: 100W | 175W | 250W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces
MLLG-USA-LED-WPFL18-30	30	3492	100W
MLLG-USA-LED-WPFL18-50	50	5821	175W
MLLG-USA-LED-WPFL18-70	70	8150	250W
Lumens Per Watt	117		
Voltage	100-277V [D]		
Frequency	50-60Hz		
Power Factor	> .90		
THD	< 20%		
Life Hours	100,000 hours		
Color Temperature	5000K		
CRI	80+		
Beam Angle	Type 4		
Operating Temperature	-40°C to +50°C		
IP Rating	IP65		
Dimmable	0-10V		
Housing	UL Listed for Wet Locations		
Dimensions	18"W X 9"H X 9.3" D		
Weight	16		
Warranty	10 years		

Features

- Field Select Driver (30W-50W-70W) - Preset to 70W
- LED Wall Pack with heavy duty two piece die-cast aluminum housing with a textured bronze UV resistant
- Specular anodized aluminum reflector.
- Silicone gasketing provides protection against moisture.
- Mounts directly to 3.5 octagon or 4 square outlet box.
- 1/2 NPS tapped holes provided in three locations for surface conduit entry or optional photo control.
- Clear prismatic borosilicate glass refractor is thermal and shock resistant.
- Integral cast-in aluminum hinges permit complete removal of lens frame assembly without tools.

Options

Photocell	Wire Guard	Passive Infrared Sensor
Integral Emergency LED	Full Cutoff Visor	

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191