

LED Linear - Great Value

Part No: MLLG-LED-LNHBG1-[Watts]-[Color] 1175

Replaces: 250W Metal Halide | 400W Metal Halide | 1000W Metal Halide



Models

Part Number	Watts	Lumens	Replaces	Dimensions	Net Weight
MLLG-LED-LNHBG1-80-[Color]	80	10,880	250W	24.01"L x 13.77"W x 1.65"H	8.8 lbs
MLLG-LED-LNHBG1-100-[Color]	100	13,600	250W	24.01"L x 13.77"W x 1.65"H	9.9 lbs
MLLG-LED-LNHBG1-150-[Color]	150	20,400	400W	25.19"L x 17.71"W x 1.65"H	11.4 lbs
MLLG-LED-LNHBG1-200-[Color]	200	27,200	750W	25.19"L x 17.71"W x 1.65"H	11.4 lbs
MLLG-LED-LNHBG1-310-[Color]	310	42,160	1000W	45.66"L x 13.77"W x 1.65"H	18.7 lbs

Lumens Per Watt	136
Voltage	100-277V [D]
Frequency	50-60Hz
Power Factor	> .90
THD	< 20%
Life Hours	70,000 hours
Color Temperature	4000K 5000K
CRI	80+
Beam Angle	120° 82X82° 40X120°
Operating Temperature	-30°C to +60°C
Dimmable	0-10V Optional
Mounting	Chain mounts with V-clips, Cable hanging with V-clips, Pendant mount, Ceiling mount
Warranty	5 years

Features

High quality LED chips.
High quality Mean Well drivers.
Integrated sheet steel heat sink, LED TC<60°C (@ 25°C ambient).
0-10V dimming.
Dimming Motion sensor and photocell optional.

Options

Photocell	Motion Sensor	Dimming	Emergency Backup
Aisle Lens or Medium Lens	Clear or Frosted	Wire Guard	