

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Linear - Great Value

Replaces: 250W | 400W | 1000W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces	Dimensions	Net Weight
MLLG-LED-LNHBG1-80-[Color]	80	10880	250W	24.01"L x 13.77"W x 1.65"H	8.8 lbs
MLLG-LED-LNHBG1-100-[Color]	100	13600	250W	24.01"L x 13.77"W x 1.65"H	9.9 lbs
MLLG-LED-LNHBG1-150-[Color]	150	20400	400W	25.19"L x 17.71"W x 1.65"H	11.4 lbs
MLLG-LED-LNHBG1-200-[Color]	200	27200	750W	25.19"L x 17.71"W x 1.65"H	11.4 lbs
MLLG-LED-LNHBG1-200-[Color]	200	27200	750W	45.66"L x 13.77"W x 1.65"H	18.7 lbs
MLLG-LED-LNHBG1-310-[Color]	310	42160	1000W	45.66"L x 13.77"W x 1.65"H	18.7 lbs

Lumens Per Watt	136
Voltage	100-277V [D]
Frequency	50-60Hz
Power Factor	> .90
THD	< 20%
Life Hours	70,000 hours
Color Temperature	4000K 5000K
CRI	80+
Beam Angle	120° 82X82° 40X120°
Operating Temperature	-30°C to +60°C
Dimmable	0-10V Optional
Mounting	Chain mounts with V-clips, Cable hanging with V-clips, Pendant mount, Ceiling mount
Warranty	6 years

Features

- High quality LED chips.
- High quality Mean Well drivers.
- Integrated sheet steel heat sink LED TC 60 C (@ 25 C ambient).
- 0-10V dimming.
- Dimming Motion sensor and photocell optional.
- Frosted and clear cover optional.
- Chain mounts with V-clips Cable hanging with V-clips Pendant mount Ceiling mount optional.
- Wire guard optional.

Options

Photocell	Motion Sensor	Dimming
Aisle Lens or Medium Lens	Clear or Frosted	Wire Guard

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191