

## Linear High Bay - Value Price

Part No: MLLG-LED-LNHBG1-[Watts]-[Color] 1175

Replaces: 250W Metal Halide | 400W Metal Halide | 1000W Metal Halide



### Specifications

Part Number	MLLG-LED-LNHBG1-80-[Color]	MLLG-LED-LNHBG1-100-[Color]	MLLG-LED-LNHBG1-150-[Color]	MLLG-LED-LNHBG1-200-[Color]	MLLG-LED-LNHBG1-310-[Color]
Watts	80W	100W	150W	200W	310W
Lumens	10,880	13,600	20,400	27,200	42,160

Replaces	250W Metal Halide   400W Metal Halide   1000W Metal Halide				
Lumens Per Watt	136				
Voltage	100-277V [D]				
Frequency	50-60Hz				
Power Factor	> .90				
THD	< 20%				
Life Hours	70,000 hours				
Color Temperature	4000K   5000K				
CRI	80+				
Beam Angle	120°   82X82°   40X120°				
Operating Temperature	-30°C to +60°C				
Dimmable	0-10V   Optional				
Dimensions	24.01"L x 13.77"W x 1.65"H	24.01"L x 13.77"W x 1.65"H	25.19"L x 17.71"W x 1.65"H	25.19"L x 17.71"W x 1.65"H	45.66"L x 13.77"W x 1.65"H
Net Weight	8.8 lbs	9.9 lbs	11.4 lbs	11.4 lbs	18.7 lbs
Mounting	Chain mounts with V-clips, Cable hanging with V-clips, Pendant mount, Ceiling mount				
Warranty	5 years				

### Features

High quality LED chips.
High quality Mean Well drivers.
Integrated sheet steel heat sink, LED TC<60°C (@ 25°C ambient).
0-10V dimming.
Dimming Motion sensor and photocell optional.

### Options

Photocell	Motion Sensor	Dimming	Emergency Backup
Aisle Lens or Medium Lens	Clear or Frosted	Wire Guard	