

# MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

## 150-200 Watt - replace up to 750W HID

Replaces: 400W | 750W Metal Halide



### Models and Specifications

Part Number	Watts	Lumens	Replaces	Dimensions
MLLG-LED-RETRO5[A]-150-[Color]-[HV]	150	23,250	400W	6.7" L X 5.9" W X 2.75" D
MLLG-LED-RETRO5[A]-200-[Color]-[HV]	200	30,800	750W	7.9" L X 5.9" W X 2.75" D

<b>Lumens Per Watt</b>	154-155
<b>Voltage</b>	100-277V [D]   347-480V [HV]
<b>Frequency</b>	50/60 hz
<b>Life Hours</b>	100,000 (L70) hours   50,000 hrs - driver
<b>Color Temperature</b>	4000K   5000K
<b>CRI</b>	75+
<b>Beam Angle</b>	120°
<b>Operating Temperature</b>	-25°C to +55°C
<b>Dimmable</b>	0-10V   Optional
<b>Mounting</b>	Multiple mounting options
<b>Weight</b>	6
<b>Warranty</b>	10 years

### Features

- Our Large Series Retrofit wins in life rating wattage savings payback CRI and the ability to retrofit in 99% of existing Metal Halide and High Pressure Sodium fixtures.
- LED Source: Nichia Corporation
- Beam Angle: 120
- IP Rating: these units are not IP65 or above rated they need to be installed inside an IP65 if used outdoors or in a wet environment.
- Driver: Meanwell 100-277V or 480V High Voltage
- Certifications: ETL CE ROHS
- DLC Premium Qualified
- Up to 750W HID replacement

### Options

347V-480V

|4000K

|BAA (Buy America Act)