

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

Wall Pack Flood - 14"

Replaces: 70W | 100W | 150W Metal Halide



Models and Specifications

| Part Number | Watts | Lumens | Replaces |
|------------------------------|--|--------|----------|
| MLLG-USA-LED-WPFL-20 | 20 | 2340 | 70W |
| MLLG-USA-LED-WPFL-30 | 30 | 3510 | 100W |
| MLLG-USA-LED-WPFL-40 | 40 | 4680 | 150W |
| Lumens Per Watt | 115 | | |
| Voltage | 100-277V [D] | | |
| Frequency | 50-60Hz | | |
| Power Factor | > .90 | | |
| THD | < 20% | | |
| Life Hours | 100,000 (L70) hours | | |
| Color Temperature | 4000K 5000K | | |
| CRI | 80+ | | |
| Beam Angle | 120 | | |
| Operating Temperature | -30°C to +50°C | | |
| IP Rating | IP66 | | |
| Dimmable | 0-10V | | |
| Housing | Die cast Aluminum with Bronze Powder Coat Finish | | |
| Mounting | Wall Mount | | |
| Dimensions | 14" L X 9" H x 7" D | | |
| Weight | 10 lbs | | |
| Warranty | 10 years | | |

Features

- Field Select Driver (20W-30W-40W) - Preset to 40W
- LED Wall Pack with bronze powder coated paint finish is standard
- Heavy-duty two-piece die-cast aluminum housing is top-hinged for easy maintenance.
- Two captive stainless steel door fasteners.
- 1/2 threaded conduit entry with coin plug.
- Rebate eligible
- Clear prismatic borosilicate glass reflector is thermal/shock resistant.
- Computer designed and precision formed specular aluminum reflector.

Options

Photocell

| Motion Sensor

| Emergency Backup

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191