

MY LED LIGHTING GUIDE

YOUR GUIDE TO ENERGY EFFICIENT LED LIGHTING

LED Trapezoidal Full Cutoff Wall Pack

Replaces: 100W | 150W | 250W Metal Halide



Models and Specifications

Part Number	Watts	Lumens	Replaces
MLLG-USA-LED-WPFC14-30	30	3799	100W
MLLG-USA-LED-WPFC14-40	40	4863	150W
MLLG-USA-LED-WPFC14-60	60	7670	250W
Lumens Per Watt	127		
Voltage	100-277V [D] 480V [HV]		
Frequency	50-60Hz		
Power Factor	> .90		
THD	< 20%		
Life Hours	100,000 (L70) hours		
Color Temperature	3000K 4000K 5000K		
CRI	70+		
Beam Angle	> 120		
Operating Temperature	-40°C to +50°C		
IP Rating	IP65		
Dimmable	0-10V		
Housing	Die Cast Aluminum with powder coat		
Mounting	Wall Mount		
Dimensions	13"L X 9" W X 11.25"D		
Weight	14		
Warranty	10 years		

Features

- Field Select Driver - preset to 40W
- Heavy duty two piece die-cast aluminum housing.
- Silicone gasketing provides protection against moisture.
- Mounts directly to 3.5 octagon or 4 square outlet box.
- .5 NPS tapped holes provided in three locations for surface conduit entry for optional photocell control.
- Dark bronze powder coated finish for impact corrosion and UV resistance.
- Integral cast-in aluminum hinges.
- Dark Sky compliant when ordered at 3000K

Options

Photocell

| Motion Sensor

| Emergency Backup

Product enhancements may result in specification changes without notice. Contact us for the latest information

www.MyLEDLightingGuide.com (888) 423-3191